
Multiple type Home Videophone






Diagram



Dimension



[KIV-102/D102]

- For single house & multi apartment, condominium & villa system (upto 450 houses) are available
- Up to 5 indoor units (4 monitor & 1 audio handset, KIP-603) and 2 front door cameras connection
- Internal call & conversation function between extended indoor units in a house
- Audio + video conversation with visitor
- Door open (front door & common gate) function
- Call & conversation function with guard master (KIP-120)
- Monitoring function from front door camera & common gate camera (KLP-100)
 Upto 4pcs of common gate cameras connection in a building
 KIV-102 : AC Type, KIV-D102 : DC type

Specifications

Model no.	KIV-102		KIV-D102
Power	Trans AC220V ± 10%		DC17V / AC24V (Dual voltage)
Power consumption	Max. 24W, Stand by 1W		
Assurance temperature	0°C~+50°C		
Communication systems	Two way hands free conversation		
CRT	4" Flat Tube		
Wiring	4wires (front door camera), 6wires (common gate camera)		
Max. wiring distance	Ø 0.65 single cable : 50m, 5C-2V coaxial cable : 100m (front door camera)		
Mount type	Surface mount		
Dimension (mm)	190(W) x 216(H) x 48(D)		
Weight (Approx.)	1.6kg		
Camera connection	Front door camera	KC-C61,	KC-D30 (metal pinhole), KC-MB20 (metal pinhole
	Common gate camera	KLP-100, KLP-104, KLP-108, KLP-112	
		KLP-P10	0, KLP-P104, KLP-P108, KLP-P112

The product may include option or additional functions.

[Multi-entry Type Configuration]

