Sentry RC Rx1 Programming

SENTRY ROLLING CODE RX
1Press/Hold prog butt until led starts flashing, this will master erase **PROGRAMMING** Max 32 Txs
2Press/Release prog butt , press/release Tx butt , press release prog butt , press/release Tx butt and so on.Once complete press/hold prog butt until led comes on.This accepts txs
3If you have learnt 12 Txs and need to add 1 more, then:press/release prog butt 13x and carry on from step 2 .

E.T Condo Rx Programming

ET CONDO RX , TX LEARN
1Press/Hold Tx butt / Press the Set butt
2The display will show which slot it allocated
Note Max of 999 Txs
ET CONDO RX , ERASE
1Place jumper across Erase pins
2Press Up/Down butt to allocate memory location
3Press/Hold set until 000 displays

DTS RX1000 Programming

SELECTING COMPLEX OR FACTORY MODE
1Remove power
2Press/Hold the UP and DOWN butt, apply power
3FAC will flash for “factory” mode,(999)
4CON will flash for “condominium” mode (99+9)
ADDING A REMOTE
1Press/Hold UP and DOWN butt to enter programming
2Select unit number using UP or DOWN butt
3Press/Release SET butt, P1.1(or unit number selected)
4Press/Release Tx, display will change to P2.1
5Press/Release Tx again,”hop” will be displayed and then next available unit number
6Repeat steps 3 to 5 for additional Tx programming
DELETING A REMOTE
1Press/Hold UP and DOWN to enter programming
2Select unit number using UP or DOWN butt
3Press/Hold SET butt for 5 seconds
4Unit display will change to EE.1
5Remote successfully deleted
6Unit will flash deleted code
Repeat steps 2 to 5 for additional Tx deletion
DELETING ALL REMOTES
1Enter program,Press/Hold SET for 10 seconds
2While still holding SET,Press/Hold the UP butt for 10 secs
3Display will flash - - E and then E E E.

Tableview Branch:

207 Blaawberg Rd

Faircape Lodge

Tableview

Tel: 087 150 4629

Cell: 083 628 2483

mikec@automationafrica.co.za

Kenilworth Branch:

Unit 5, Warrington Rd

Venus Business Park

Kenilworth

Tel: 021 674 6329

Tel: 087 150 4623

kenilworth@automationafrica.co.za

Strand Branch:

Unit 14, Potgieter Rd

Trade Link Park

Strand

Tel: 021 854 6299

Tel: 087 150 4628

strand@automationafrica.co.za

Brackenfell Branch:

Unit K11, Kenwill Drive

Okovango Junction

Brackenfell

Tel: 021 982 6338

Tel: 087 150 4626

jacoj@automationafrica.co.za

Technical Contacts:

Jaco Jonker: 082 417 6510

Robin Rolfe: 082 777 5301

Mark Bristow: 072 997 3640

Mike Correia: 083 628 2483

automationafrica

www.automationafrica.co.za

DISTRIBUTORS OF ACCESS CONTROL EQUIPMENT

automationafrica

ACCESS CONTROL QUICK REFERENCE GUIDES

www.automationafrica.co.za

DTS 512/624 Slider Setup

DTS 512/624 SLIDER SET UP DTS PCB

1All dipswithes off
2Move dipswitch 2 on or off to select direction
3Open gate approx 1 mtr
4Press / release BT Set button
5Gate will close / open /close
6PCB will beep to confirm set up

Note If gate opens first,switch dipswitch 2

AUTO CLOSE

1Switch dipswitch 1 and 3 on
2Press and hold BT Set button
3Every beep counts for 1 second
4Release Bt/Set butt at required time
5Switch 1 and 3 off
6Switch 3 on to activate autoclose

Note Default is 15 seconds

PED OPENING

1Gate in closed position
2Switch dipswitch 1 and 4 on
3Press/Release Bt/Set butt,gate will start opening,press/release Bt/Set butt at required ped opening
4Press/Hold Bt/Set butt,every beep counts for 1 second of auto close time
5Release Bt/Set at required time
6Switch dipswitch 1 and 4 off

Note Default at 1 Mtr and 4 Sec closing

REMOTE PROGRAM FOR FULL OPENING

1Press/Release Bt Lrn butt,Rx led will go on
2Press/Release Tx butt,2 beeps will be heard
3Repeat steps 1 and 2 to add more remotes

Note Up to 25 remotes can be programmed

REMOTE PROGRAM FOR PEDESTRIAN OPENING

1Press/Release Pd Lrn butt
2Press/Release Tx butt,2 beeps will be heard
3Repeat steps 1and 2 for more remotes

Note Up to 5 remotes can be programmed

DTS 512/624 Beep Indications

*2 long beeps before movement-No AC Power
*2 short beeps-TX programmed
*3 short beeps then movement-Ped Trigger
*3 short beeps follwed by 3 short beeps-Battery Low
*4 quick beeps, no movement-Holiday Lockout
*Relay clicks,no movement, 4 short beeps-Motor Fuse Blown
*Short movement followed by 4 short beeps-Not reading encoder
*Very short movement,4 short beeps,status led flashes fast-Overload
*5 long beeps-Holiday lockout de-activated
*2 short beeps-Setup completed
*1 long beep-Autoclose overridden

DTS 600 Eazi-Auto Gdo Setup

DTS EAZI-AUTO 600 LIMIT SETUP

1Door must be engaged in the middle position
2Power on
3Press/Hold K1 until a 1 appears on screen
4Press K3 until door is in open position
5If overrun,press K4 to correct
6Press/Release K1 to accept
7Press K4 until door is in the closed position
8Press/Release K1 to accept
9The door will open / close to set sensitivity
Set up is now complete

DTS EAZI AUTO 600 ADD SENSITIVITY

1Press/Hold K1 until a numbers 1-3 display
2Press/Release K3 to increase force 1 degree and K4 to decrease force 1 degree
3Minimum force is 1 and Max Force is 9
4Press/Release K1 Set to accept setting

DTS EAZI AUTO 600 TX PROGRAMMING

1Press/Release K2
2Press/Release Tx, Press/Release Tx again
3To delete,Press/hold K2 until C displays

DTS EAZI AUTO 600 BEAM FUNCTION

1Press/Hold K4 , screen will display -
2Press/Release K3, a H is Displayed
Safety Beams are now enabled.
3Press/Release K4, II is displayed to disable.
4Press/Release K1 to accept setting

DTS EAZI AUTO 600 HOLIDAY LOCKOUT

1Press/Hold K1 until digits display 1 to 4
2Release K1 once 4 appears
3A 0 is displayed
4Press/Release K3 until a 1 is displayed
Press/Release K1 to accept, holiday lockout is now activated.
5Press/Release K1 when a 0 is displayed to accept, holiday lockout is now deactivated.
6Motor will allow 1 opening and closing,after closing
Allow 2 seconds for lock out to activate

DTS 12R Gdo Setup

DTS 12R LIMIT SETUP

1Remove limit switch cover plate
2Top limit cam "T" controls open position of door
3Slightly loosen screws so cams can be moved
4Disengage motor, move door open 100mm from top
5Rotate cam "T" until contact is made with limit switch
6Lower door to the ground
7Rotate cam "B" until contact is made with limit switch
8Tighten screws
6Set door halfway and engage.

DTS 12R TX PROGRAMMING

1Press/Release K1,Red IED will light up.
2Press/Release Tx, Press/Release Tx again
3To delete,Press/hold K1 until LED flashes 10 times
Maximum Remotes: 20

Centurion D3/5 Slider Setup

D3/5 LIMIT SET UP

1Pwr Off / Set Jumper On / Gate engaged in middle / Pwer On
2Press/Release Test butt,L1 will flash x1 per sec
3Press/Hold test butt until status led lights up , then release.
4Gate will open/close/open/close/stop at ped
5Remove set jumper and press test butt

Centurion D2 Slider Setup

D2 LIMIT SET UP

1Pwr Off / Set Jumper On / Gate engaged in middle / Pwer On
2Press/Release Test butt,L1 will flash x1 per sec
3Press/Hold test butt,Release butt when Status led flashes x1 if gate closes to the left and after x2 flashes if gate closes to the right
4Gate will open/close/open/close/stop at ped

Centurion R5 Swing Gate Setup

R3/5 MASTER LIMIT SET UP

1Pwr Off,Close gate manually,and turn set knob until arrow lines up,open gate 1/2 way
2Turn Alan key out so that it is level with shaft
3Fit set jumper and apply pwr
4Press/Release test butt,L1 will flash x1 per sec
Press/Hold test butt until led flashes x1 then release for master set up.Press/hold test butt, the mtr will run and after approx 60 sec the gate will start closing.release the butt in the closed position,press/hold the test butt , the gate will open,release when open.
5Press / Release test butt , the gate closes and then opens to ped position.
6Remove set jumper and press/release test butt

Note If gate opens first then swop the motor wires

R3/5 SLAVE LIMIT SET UP

1Pwr Off,Close gate manually,and turn set knob until arrow lines up,open gate 1/2 way
2Turn Alan key out so that it is level with shaft
3Fit set jumper and apply pwr
4Press/Release test butt,L1 will flash x1 per sec
Press/Hold test butt until led flashes x2 then release for slave set up.Press/hold test butt, the mtr will run and after approx 60 sec the gate will start closing.release the butt in the closed position,press/hold the test butt , the gate will open,release when open.
5Press / Release test butt , the gate will close
6Remove set jumper and press/release test butt

Note If gate opens first then swop the motor wires